Tommy Car Wash Systems
648 S POINT RDG
HOLLAND, MI 49423-9418 • United States
Sales: (616) 494-0411 • Support: (616) 795-4892
sales@tommycarwash.com | www.tommycarwash.com
*Prices subject to change without notice and do not include tax, shipping, or installation

2" Cam and Groove Type D Coupler x 2" FNPT (304 SS)

Part Number: P-WAT-3291

Description: CAM-20-D-SS304 Type D Cam and Groove Coupler with a 2" Female Camlock quick connect on one side and a 2" FNPT thread on the other. Made from corrosion-resistant 304 Stainless Steel with a Buna-N seal

Price: $40.99

Detailed Description

This Type D cam and groove coupler is essential for connecting a male-threaded pipe to a camlock hose or adapter. Its female camlock end easily and securely attaches to a 2" male camlock adapter, providing a quick-disconnect point in various industrial applications.

Key features and benefits include:

- **Connection Versatility:** One side offers a 2" Female Camlock for fast, tool-free connection/disconnection, while the other side offers a 2" Female NPT thread to connect to a permanent male-threaded pipe or fixed component.
- **Corrosion Resistance:** The body and cam arms are made of durable 304 Stainless Steel, which is highly resistant to corrosion and abrasion, ensuring long life with water, oils, and other chemicals.
- **Sealing:** Includes a Buna-N (NSS) seal, which is resistant to fuels, oils, coolants, and petroleum products, providing reliable leak-proof connections.
- **Performance:** Complies with commercial item description A-A-59326D for quick disconnect fittings, offering a maximum pressure rating of 250 PSI.
- **Use Case:** Popular in applications requiring quick connection/disconnection such as in car wash water treatment, the wastewater industry, fuel delivery, and general fluid transfer.

Warning: Type D cam and groove fittings, or any other camlock fitting, should not be used for compressed air or steam due to the risk of dangerous fragmentation.

Specifications

- Manufacturer Part No. (Mfr): CAM-20-D-SS304
- Product Type: Cam and Groove Coupler Fitting
- Camlock Type: Type D
- Connection Sizes: 2" Female Camlock x 2" Female NPT
- Material: 304 Stainless Steel Body and Cam Arms
- Seal/Gasket Type: Buna-N (NSS)
- Max Pressure Rating: 250 PSI